



Модуль Cisco C6800-16P10G-XL

C6800-16P10G-XL

Описание

16-портовый модуль 10GE SFP+ для коммутаторов Cisco Catalyst серии 6500-E и шасси C6807-XL.

Основные особенности:

- 16 портов 10GE SFP+
- Переподписка: 16 портов 2:1 (default mode), 8 портов 1:1 (performance mode)
- Подключение к фабрике 80 Gbps (в шасси серии C6500-E и C6807-XL)
- Память по дефолту 2GB (максимум)
- Поставляется с модулем DFC4XL
- Таблица MAC адресов 128K
- Поддержка Jumbo Frame 9216 байт

Общие

Тип устройства	Карты расширения
Линейка Cisco	Catalyst 6800
Совместимая платформа	Шасси WS-C6503-E Шасси WS-C6504-E Шасси WS-C6506-E Шасси WS-C6509-E Шасси WS-C6509-V-E Шасси WS-C6513-E Шасси C6807-XL
Поддерживаемый тип интерфейсов модульного коммутатора	Интерфейсы 10GBase-X SFP+
Совместимость с управляющими модулями	C6800-SUP6T VS-S2T-10G VS-S2T-10G-XL

Доп. описание



OOO NAGTECH
+998 55 508 0660
sales@nag.uz

Non-XL	XL
256K IPV4 and MPLS Forwarding entries, 128K IPV6 entries 64K IPV4/IPV6 Multicast routes 64K ACL entries (shared between QoS and security) 1M NetFlow entries (32 port card, with 2 forwarding engines) 512K NetFlow entries (8/16 port card, with 1 forwarding engine)	1M IPV4 and MPLS Forwarding entries, 512K IPV6 entries 64K IPV4/IPV6 Multicast routes 256K ACL entries (shared between QoS and security) 2M NetFlow entries (32 port card, with 2 forwarding engines) 1M NetFlow entries (8/16 port card, with 1 forwarding engine)