



# Точка доступа Cisco C9117AXI-E

### Описание

Блок питания AIR-PWRINJ5, AIR-PWRINJ6 и крепления в комплект не входят

#### Ключевые особенности:

Стандарт 802.11ах с технологией многоканального входа-выхода (MIMO) 8x8 с восьмью пространственными потоками при 5-GHz обеспечивает теоретическую скорость передачи до 5 Гбит/с Поддержка каналов до 160 МГц

1 порт со скоростью до 5G Base-T

#### Обзор продукта

Catalyst 9117 Series масштабируется в соответствии с растущими требованиями Интернета вещей при полной поддержке последних инноваций и новых технологий. Catalyst 9115 Series также является лидером по производительности, безопасности и аналитике.

C Catalyst 9117 Series вы можете защитить удаленных сотрудников или микро-офис. Любая точка доступа Cisco Aironet или Catalyst может работать как точка доступа OfficeExtend (OEAP). С OEAP сотрудник дома или во временном микро-офисе будет иметь доступ к корпоративному SSID и корпоративной сети без необходимости настраивать VPN.

| Feature                  | Benefits  |  |
|--------------------------|---|--|
| 802.11ax (Wi-Fi<br>6)    | The IEEE 802.11ax emerging standard, also known as High-Efficiency-Wireless (HEW) or Wi-Fi 6, builds on 802.11ac. It will deliver a better experience in typical environments and more predictable performance for advanced applications such as 4K or 8K video, high-density, high-definition collaboration apps, all-wireless offices, and IoT. 802.11ax is designed to use both the 2.4-Ghz and 5-GHz bands, unlike the 802.11ac standard. |  |
| Uplink/downlink<br>OFDMA | OFDMA-based scheduling splits the bandwidth into smaller chunks called Resource Units (RUs), which can be allocated to individual clients in both the downlink and uplink directions to reduce overhead and latency.  |  |
| MU-MIMO<br>technology    | Supporting four spatial streams, MU-MIMO enables access points to split spatial streams between client devices, to maximize throughput.   |  |
| BSS coloring             | Spatial reuse (also known as Basic Service Set [BSS] coloring) allows the Access Points (APs) and their clients to differentiate between BSSs, thus permitting more simultaneous transmissions.   |  |
| Target wake<br>time      | A new power savings mode called Target Wake Time (TWT) allows the client to stay asleep and to wake up only at prescheduled (target) times to exchange data with the AP. This offers significant energy savings for battery-operated devices. up to 3x to 4x compared to 802.11n and 802.11ac.  |  |



# OOO NAGTECH +998 55 508 0660 sales@nag.uz

|  | 5g, 50gc .0. 00, 5p.5.0 00, 5p.5.0 00pa.50   |  |
|--|--|--|
| Cisco<br>Embedded<br>Wireless<br>Controller          | The 9115 Wi-Fi 6 access points are available with a built-in controller. The Cisco Embedded Wireless Controller on Catalyst 9100 Access Points provides an easy-to-deploy and manage option that does not require a physical appliance. The control resides on the access point, so there is no added footprint or complexity. And because it uses Cisco Catalyst 9800 Series code, it's easy to migrate your network as your needs grow. For more details refer to EWC                                      |  |
| User Defined<br>Network                              | A feature available in Cisco DNA Center, allows IT to give end users control of their very own wireled network partition on a shared network. End users can then remotely and securely deploy their devices on this network. Perfect for university dormitories or extended hospital stays, Cisco User Defined Network grants both device security and control, allowing each user to choose who can connect to their network. (Available second half of calendar year 2020.) For more details refer to UDN. |  |
| Application<br>Hosting on<br>Catalyst 9100<br>Access | Application Hosting on Catalyst 9100 Access Points helps future-proof and simplify IoT deployments by eliminating the need to install and manage overlay networks. Utilizing the USB interface, containerized applications and hardware modules can be deployed to reduce cost and complexity. Adding Cisco DNA Center provides workflows and deployment-wide application lifecycle management.  |  |
| Multigigabit<br>Ethernet<br>support                  | Provides uplink speeds of 2.5 Gbps, in addition to 100 Mbps and 1 Gbps. All speeds are supported or Category 5e cabling for an industry first, as well as 10GBASE-T (IEEE 802.3bz) cabling.  |  |
| Bluetooth 5.0  | Integrated Bluetooth Low Energy (BLE) 5.0 radio to enable IoT use cases such as location tracking and wayfinding.  |  |
| Apple features                                       | Apple and Cisco have partnered to create an optimal mobile experience for iOS devices on corporate networks based on Cisco technologies. Using new features in iOS 10, in combination with the latest software and hardware from Cisco, businesses can now more effectively use their network infrastructure to deliver an enhanced user experience across all business applications.  |  |
|  | At the center of the collaboration is a unique handshake between the Cisco WLAN and Apple devices. This handshake enables the Cisco WLAN to provide an optimal Wi-Fi roaming experience to Apple devices. Additionally, the Cisco WLAN trusts Apple devices and gives priority treatment for business-critical applications specified by the Apple device. This feature is also known as Fast Lane.  |  |
|  |  |  |

# Общие

| Частотный диапазон Wi-Fi, ГГц      | 2.4<br>5                      |
|------------------------------------|-------------------------------|
| Поддержка МІМО, в диапазоне 2.4ГГц | 4x4                           |
| Поддержка МІМО, в диапазоне 5ГГц   | 8x8                           |
| PoE                                | 802.3at<br>802.3af<br>802.3bt |
| Портов LAN                         | 1                             |



## OOO NAGTECH +998 55 508 0660 sales@nag.uz

Стандарты Wi-Fi IEEE 802.11

Уличный корпус

Температура окружающей среды рабочая, °С

Порт USB

Тип антенны

802.11g

802.11ax (Wi-Fi 6)

802.11a

802.11n (Wi-Fi 4)

802.11ac (Wi-Fi 5)

Нет

от -30 до 70

USB 2.0

всенаправленная